

(Please Use this Form for Filling your Local Law with the Secretary of State)

Text of law should be given as amended. Do not include matter being eliminated and do not use italics or underlining to indicate new matter.

~~COUNTY~~  
~~TOWN~~ of ..... Easton .....  
Town  
~~VILLAGE~~

Local Law No. .... One ..... of the year 19 89 .....

A local law amending the local law requiring driveway permits and establishing procedures for the issuance thereof (Insert title)

Be it enacted by the ..... Town Board ..... of the (Name of Legislative Body)

~~COUNTY~~  
~~TOWN~~ of ..... Easton ..... as follows:  
Town  
~~VILLAGE~~

AMENDMENTS TO LOCAL LAW NO. TWO, 1988,  
REQUIRING DRIVEWAY PERMITS AND ESTABLISHING PROCEDURES  
FOR THE ISSUANCE THEREOF AS ADOPTED BY THE TOWN BOARD  
OF EASTON ON SEPTEMBER 6, 1988

Add to Section 2: Definitions.

Grade or slope - (measured by percentage) means that a change in elevation of one foot each 100 feet equals one percent. If the grade or slope is irregular the percentage will be calculated at 25 foot intervals and each interval shall be within the standards set by the Town Laws and Regulations.

Section 5: Design.

The angle of the first twenty-five (25) feet of the driveway with respect to the highway edge shall be as close as possible to 90 degrees, with an allowable range between 60 degrees and 90 degrees. The driveway shall be designed so that all vehicles that will use it on a regular basis may enter the driveway from the highway going forward and will be able to turn around and enter the highway from the driveway going forward. If full length of the driveway is not visible from either end, then the driveway must be constructed and maintained year-around with a midway area adequate to accomodate two way traffic under emergency situations. The width of the driving surface of the driveway at the point of highway access shall not be greater than thirty-five (35) feet.

Section 6: Grade.

The first twenty-five feet of the driveway shall not have a grade in excess of 5%. The maximum grade for residential driveways shall not be greater than 12% and for commercial driveways not greater than 10%. If the slope from the edge of the driveway shoulder is greater than 1 on 4 where the driveway is more than 6 feet above the original surface of the ground then Town approved guide rails shall be installed.

(If additional space is needed, please attach sheets of the same size as this and number each)

Be it enacted this 2nd day of May, 1989, by the Town Board of Town of Easton of Washington County, New York, to be effective immediately upon filing with the Secretary of State.

*Effective 5/8/89*

George B. Rogers Sr.

Alan P. Biny

James W. Bodens

R. Harry Booth

SEAL

Shirley Lamb

ATTEST: Town Clerk